








11149		MITSUBISHI OUTLANDER 2.2 DI-D		MITSUBISHI NR / NO:	2
				ÅRSMODEL / YEAR:	2010 -
				MODELLKODE / CODE:	
				LAND / COUNTRY:	
					
4HK	411707	460492	766	785	B

INSTALLATION:

Use heater no. **707** + mounting kit no. **460492** in **H**. Mounting time: **B**

Dismount the cover over the engine. Dismount the original hose (1) between the engine and the oil cooler. Fit the protection tube (2) onto the angled 200x130mm hose (3).

Fit the angled 200x130mm hose (3) on the engine. **Note!** Connect the longest hose end to the engine.

The protection tube (2) shall protect the sharp edge on the oil cooler.

Fit the 50x50mm angled hose (4) to the oil cooler pointing cross upwards.

Fit one of the enclosed spool pieces (5) in the angled hose (4).

Fit the 50x270mm angled hose (6) onto the spool piece. **Note!** Connect the shortest hose end onto the spool piece. Fit the bracket (7) and the fastening iron (8) onto the heater and fit it to the free bracket hole on the cable fastener (9).

Fit the 50x140mm angled hose (10) onto the lower engine heater pipe stub. **Note!** The shortest end onto the heater.

Fit the other spool piece (11) in the hose (10), and then connect the hose (6) from the oil cooler onto the spool piece (11).

Fit the hose (3) from the engine on top of the heater.

Adjust the heater into vertical position. Ensure that no hoses is scratching nor touching other engine parts.

Top up with the coolant specified by the car manufacturer, and bleed the cooling system in accordance with the car manufacturers instruction book. Check for leakages.

